

Fixatie van Buzon® vloerdragers met kit

How to apply ?

DERBISEAL S

Instructions for use

A/ Surface preparation



- Apply DERBISEAL S on a clean, dry and grease-free surface.
- On absorbent surfaces, first apply DERBIPRIMER (S, GC or E), and allow to dry.

B/ Apply DERBISEAL S for fixing adapted insulation boards



- Using suitable fittings apply DERBISEAL S by strips with hand pump K2, pneumatic pump K4 or screw pump K15. Or apply DERBISEAL S by blobs using a roofer's trowel.
- On steel deck (*): depending on the steel deck geometry and the wind uplift calculation, apply per corrugation one strip of DERBISEAL S in the central roof area and two strips in the perimeter and corner zones. The lengths of the insulation boards are to be perpendicular to the corrugations of the deck.
- On continuous substrates (*), like old roofing, underlayer or vapour barrier: DERBISEAL S may be applied by strips to the surface or by blobs to the underside of the insulation boards.
- Lay and press down immediately the insulation boards in the freshly applied DERBISEAL S. Make sure they fit tightly and position them staggered for better stability. It may be necessary to add an additional load around the perimeter.

C/ Apply DERBISEAL S to seal DERBIGUM overlaps



- 'No Flame' sealing of DERBIGUM overlaps (lengthwise 12 cm, transverse 15 cm) is possible using DERBISEAL S. As these 'No Flame' application techniques demand very specific skills, do not hesitate to contact the Imperbel Technical Department for further information. Alternatively attend a specific 'No Flame training' at the Imperbel Training Center.
- DERBISEAL S can be applied on :
 - zinc
 - metal deck
 - old bituminous membranes
 - DERBICOAT type vapour barrier.

(*You can find more specific information on the data sheet.


WWW.DERBIGUM.COM

DERBIGUM
de Zekerheid is alleen

DERBIGUM NEDERLAND B.V.
Old Polmar: 2926
Postbus 237 - 9200 AE Drif
Tel: 015/213 40 00 - Fax: 015/213 40 11
Email: info@derbigum.nl

BEST IN ROOFING
DERBIGUM





Fixatie van Buzon® vloerdragers met lijm

